RF Devices, Inc.

PRODUCT SPECIFICATION FOR INFORMATION(Preliminary-spec)


- **Customer :**
- **Product Name : RMB4D-Type (4D-MONO)**
- **Part No : RMB4D1820B22PB**

Items	Specification(@25℃)	Unit
Center frequency(Fo)	1820	MHz
Bandwidth	22	MHz
Insertion Loss in BW	3.0	max
Ripple in BW	0.5	max
VSWR in BW	1.3	max
Attenuation	45 @ 1596MHz	min
In/Out Impedance	50 Ω	
Input power	3W	
Operation Temperature	-40℃ to +85℃	


Note ; Equipment Used : 8753ES

Dimension


TOP VIEW



BOTTOM VIEW



FRONT VIEW



I/O PORT

GROUND


TOLERANCE:± 0.2

UNIT: mm

본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved

RF Devices, Inc.

S-Parameters



본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved