RF Devices, Inc.

PRODUCT SPECIFICATION FOR INFORMATION(Preliminary-spec)

- **Customer :**
- **Product Name : RMB-2R-SM-Type**
- **Part No : RMB-2R-SM-642B5B**


Items	Specification(@25℃)	Unit
Center frequency(Fo)	642	MHz
Bandwidth	5	MHz
Insertion Loss in BW	2.5	max
Ripple in BW	0.5	max
VSWR in BW	1.5	max
Attenuation		min
	25 @ 874~894MHz	
In/Out Impedance	50 Ω	
Input power	3W	
Operation Temperature	-40℃ to +85℃	


Note ; Equipment Used : 8753ES

Dimension

BOTTOM VIEW

SIDE VIEW






TOLERANCE UNLESS OTHERWISE SPECIFIED : ±0.2
DIMENSIONS : mm

GROUND
I/O PORT

본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved

RF Devices, Inc.

S-Parameters



본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved