RF Devices, Inc.


PRODUCT SPECIFICATION FOR INFORMATION(Preliminary-spec)

- **Customer :**
- **Product Name : RMD8J-Type**
- **Part No : RMDH8J2655D2535B70PD**

Items	Specification		Unit
Center frequency(Fo)	2535	2655	MHz
Bandwidth	2500 ~ 2570	2620 ~ 2690	MHz
Insertion Loss in BW	2.2 dB	2.2 dB	max
Ripple in BW	1.2 dB	1.2 dB	max
Return Loss in BW	15.0 dB	15.0 dB	min
V.S.R.W. in BW			max
Attenuation	45dB @ 2620 ~ 2690MHz	45dB @ 2500 ~ 2570MHz	min
In/Out Impedance	50 Ω		
Operation Temperature Range	2W		

Note ; Equipment Used : 8753ES

Dimension





FINISH : NICKEL PLATED
MATERIAL : 1/2 H BRASS
CONNECTION :
Ant Port : SMA -R/A 2H
R/Tx Port : SMA- S- 4H
TOLERANCE : ± 0.50
UNIT : mm

본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2011 RF Devices, Inc. All rights reserved

RF Devices, Inc.

S-Parameters





본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2011 RF Devices, Inc. All rights reserved