RF Devices, Inc.


PRODUCT SPECIFICATION FOR INFORMATION(Preliminary-spec)

- **Customer :**
- **Product Name :RMD10L-Type**
- **Part No : RMD10L2310A2355B10PC**

Items	Specification		Unit
Center frequency(Fo)	2310 (LOW)	2355(HIGH)	MHz
Bandwidth	Fo ± 5	Fo ± 5	MHz
Insertion Loss in BW	3.0	3.0	dB max
Ripple in BW	1.0	1.0	dB max
Return Loss in BW	15	15	dB min
Attenuation	50min(55typ)@@2350~2360 MHz	55min(60typ)@2305~2315 MHz	dB min
Isolation	50@2305~2315MHz		
	10 @2315~2350MHz		
	50@2350~2360MHz		
In/Out Impedance	50 Ω		
Input power	6W		
Operation Temperature	-40℃ to +85℃		

Note ; Equipment Used : 8753ES


Dimension




본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved

RF Devices, Inc.

S-Parameters






본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved

RF Devices, Inc.

S-Parameters (Isolation)



본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved