RF Devices, Inc.

PRODUCT SPECIFICATION FOR INFORMATION(Preliminary-spec)


- **Customer :**
- **Product Name : 6J-Type**
- **Part No : RMD6J820T865B7PB**

Items	Specification		Unit
Center frequency(Fo)	820.5MHz (low)	865.5MHz (high)	MHz
Bandwidth	Fo ± 3.5	Fo ± 3.5	MHz
Insertion Loss in BW	2.5	2.5	dB max
Ripple in BW	0.5	0.5	dB max
Return Loss in BW	18	18	dB min
Attenuation	50dB min.@ 862~869 MHz	50dB min.@ 817~824 MHz	
In/Out Impedance	50 Ω		
Input power	2W		
Operation Temperature	-40℃ to +85℃		


Note ; Equipment Used : 8753ES

Dimension


TOP VIEW



BOTTOM VIEW



FRONT VIEW



I/O PORT

GROUND

TOLERANCE : ± 0.20

UNIT: mm

본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved

S-Parameters

본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved