
RF Devices, Inc.

PRODUCT SPECIFICATION FOR INFORMATION

- **Customer :**
- **Product Name : Cavity BPF-Type**
- **Part No : RFD900-F5862.5-22M-01**


Items	Specification	Unit
Center frequency(Fo)	5862.50 MHz	MHz
Bandwidth	22 MHz (5851.5~5873.5MHz)	MHz
Insertion Loss in BW	1.5 dB(상온)	max
Ripple in BW	1.2 dB(상온)	max
Return Loss in BW	18 dB(상온)	min
Attenuation	40dBc @ 5836.5 MHz (상온)	min
	40dBc @ 5888.5 MHz(상온)	
In/Out Impedance	50Ω	
Input power	2W	
Operation Temperature	방수.블랙color,	

DIMENSION



본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved

DATA(201204001)



TEST REPORT CERTIFICATE

	201204001	201204002							
I/L	1.27	1.29							
Ripple	0.25	0.26							
R/L	24.4	24.7							
Attenuation	44.0	43.5							
	43.8	46.7							

본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved