# RF Devices, Inc.

## PRODUCT SPECIFICATION FOR INFORMATION


- **Customer :**
- **Product Name : RLB-AA-Type**
- **Part No : RLB-65-BP6MAA**

| Items | Specification | Unit |
|---|---|---|
| **Center frequency(Fo)** | 65 | MHz |
| **Bandwidth** | Fo ± 3 | MHz |
| **Insertion Loss in BW** | 3.0 | dB max |
| **Ripple in BW** | 0.5 | dB max |
| **V.S.W.R in BW** | 1.4 | dB max |
| **Attenuation** | 38 dB min. at Fo -25MHz<br>35 dB min. at Fo -25MHz | dBc min |
| **In/Out Impedance** | 50 Ω | |
| **Input power** | 3W | |
| **Operation Temperature** | -40℃ to +85℃ | |


Note ; Equipment Used : 8753ES

**Dimension**


**TOP VIEW**




**SIDE VIEW**




**BOTTOM VIEW**




**I/O PORT**


**GROUND**

**TOLERANCE : ÷ 0.20**
**UNIT: mm**

본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved

# RF Devices, Inc.

## S-Parameters




본 승인원 에 대한 소유권은 RFD에 있으며, 허가 없이 무단 복제 인용을 금함. Copyright ⓒ 2010 RF Devices, Inc. All rights reserved